



**BRI-T5-C5-H3**

Width: 19.5"  
Height: 28.5"  
Weight: 45lbs  
EPA: 2.16ft<sup>2</sup>

Brighton  
ordering guide



## ordering logic

### model

BRI-T5-C5-H3 Brighton

### lens material

A acrylic

### lens finish

C clear (acrylic only)

F frosted

R3 refractive type III

R5 refractive type V

### source

LED 24, 48 & 70W

QL 55, 85 & 165W QL induction

PSMH 50 - 200W

HPS 50 -150W

CF 13 - 42W

### optics

IND3 indirect type III (LED)

IND5 indirect type V (LED)

DIR2 direct type II (LED)

DIR3 direct type III (LED)

DIR4 direct type IV (LED)

DIR5 direct type V (LED)

SR3 segmented reflector type III

SR4 segmented reflector type IV

SR5 segmented reflector type V

GR3 glass refractor type III

GR5 glass refractor type V

### electrical options

FS fusing

PEC photocell

QRS quartz restrike

IQ lamp/ballast diagnostics

LSP lightning surge protector

### model (cont)

BRI-T5-C5-H3 Brighton

### color (see page 33 for additional information)

BB black

BZ bronze

BG green

BW white

BY gray

RAL RAL \_\_\_\_\_

OTHER \_\_\_\_\_

### footnotes:

1. Medium socket is standard for all HID sources under 250W.
2. IND and DIR optics require LED source, LED source requires IND or DIR optics. AC lens recommended.
3. Factory suggests that BL option is selected only when a low wattage source is used in conjunction with non-clear or refractive lenses.
4. LED and CF sources utilize a 120-277 voltage-sensing electronic driver, HID sources utilize a Quad-Tap (120, 208, 240 & 277V) core & coil magnetic ballast, consult factory for 347 or 480V. 12VDC LED drivers are available for solar power assembly integration, consult factory.
5. QL induction source shall be supplied at 4000K (CCT), specify if 3000K is required. AR lens with BL option is recommended.
6. LED source shall be supplied at 4500K (CCT), specify is other color temp. is required (minimum quantities may apply).