



CENA42

Width: 13.5"

Height: 42"

Centennial ordering guide

Bollards & Columns



ordering logic

model

CEN42	Centennial
-------	------------

lens material

<input type="checkbox"/>	A	acrylic
<input type="checkbox"/>	P	polycarbonate

lens finish

<input type="checkbox"/>	F	frosted
<input type="checkbox"/>	W	white

source

<input type="checkbox"/>	UL	unlighted
<input type="checkbox"/>	PSMH	50 - 70W
<input type="checkbox"/>	HPS	50 - 70W
<input type="checkbox"/>	CF	13 - 42W

optics

<input type="checkbox"/>	BL	bare lamp
--------------------------	----	-----------

electrical options

<input type="checkbox"/>	FS	fusing
<input type="checkbox"/>	PEC	photocell
<input type="checkbox"/>	IQ	lamp/ballast diagnostics

style options

<input type="checkbox"/>	CES	chain eye, single
<input type="checkbox"/>	CED	chain eye, double

mounting options

<input type="checkbox"/>	AB	anchor base
<input type="checkbox"/>	DBE	direct burial extension

color (see page 33 for additional information)

<input type="checkbox"/>	BB	black
<input type="checkbox"/>	BZ	bronze
<input type="checkbox"/>	BG	green
<input type="checkbox"/>	BW	white
<input type="checkbox"/>	BY	gray
<input type="checkbox"/>	RAL	RAL _____
<input type="checkbox"/>	OTHER	_____

footnotes:

1. Medium socket is standard for all HID sources.
2. CF sources utilize a 120-277 voltage-sensing electronic driver, HID sources utilize a Quad-Tap (120, 208, 240 & 277V) core & coil magnetic ballast.
3. Chain eye, unlit only.