



MED-T1-C1-H1

Width: 18.5"

Height: 37.5"

Weight: 45lbs

EPA: 2.16ft²

Mediterranean ordering guide

Luminaires



ordering logic

model

MED-T1-C1-H1	Mediterranean
MED-T1-NC-H1	Mediterranean (no cage)

lens material

<input type="checkbox"/>	A	acrylic
--------------------------	---	---------

lens finish

<input type="checkbox"/>	C	clear (acrylic only)
<input type="checkbox"/>	F	frosted
<input type="checkbox"/>	R3	refractive type III
<input type="checkbox"/>	R5	refractive type V

source

<input type="checkbox"/>	LED	24, 48 & 70W
<input type="checkbox"/>	QL	55, 85 & 165W QL induction
<input type="checkbox"/>	PSMH	50 - 200W
<input type="checkbox"/>	HPS	50 -150W
<input type="checkbox"/>	CF	13 - 42W

optics

<input type="checkbox"/>	IND3	indirect type III (LED)
<input type="checkbox"/>	IND5	indirect type V (LED)
<input type="checkbox"/>	DIR2	direct type II (LED)
<input type="checkbox"/>	DIR3	direct type III (LED)
<input type="checkbox"/>	DIR4	direct type IV (LED)
<input type="checkbox"/>	DIR5	direct type V (LED)
<input type="checkbox"/>	SR3	segmented reflector type III
<input type="checkbox"/>	SR4	segmented reflector type IV
<input type="checkbox"/>	SR5	segmented reflector type V
<input type="checkbox"/>	GR3	glass refractor type III
<input type="checkbox"/>	GR5	glass refractor type V

electrical options

<input type="checkbox"/>	FS	fusing
<input type="checkbox"/>	PEC	photocell
<input type="checkbox"/>	QRS	quartz restrike
<input type="checkbox"/>	IQ	lamp/ballast diagnostics
<input type="checkbox"/>	LSP	lightning surge protector

model (cont)

MED-T1-C1-H1	Mediterranean
MED-T1-NC-H1	Mediterranean (no cage)

COLOR (see page 33 for additional information)

<input type="checkbox"/>	BB	black
<input type="checkbox"/>	BZ	bronze
<input type="checkbox"/>	BG	green
<input type="checkbox"/>	BW	white
<input type="checkbox"/>	BY	gray
<input type="checkbox"/>	RAL	RAL _____
<input type="checkbox"/>	OTHER	_____

footnotes:

1. Medium socket is standard for all HID sources under 250W.
2. IND and DIR optics require LED source, LED source requires IND or DIR optics. AC lens recommended.
3. FGCH & 3CD options are optionally energized when SR optics are selected (please consult factory for accommodation).
4. Factory suggests that BL option is selected only when a low wattage source is used in conjunction with non-clear or refractive lenses.
5. LED and CF sources utilize a 120-277 voltage-sensing electronic driver, HID sources utilize a Quad-Tap (120, 208, 240 & 277V) core & coil magnetic ballast, consult factory for 347 or 480V. 12VDC LED drivers are available for solar power assembly integration, consult factory.
6. QL induction source shall be supplied at 4000K (CCT), specify if 3000K is required. AR lens with BL option is recommended.
7. LED source shall be supplied at 4500K (CCT), specify if other color temp. is required (minimum quantities may apply).