



- 30" Traditional Luminaire
- Custom Arm

**TRA30**

Width: 14.25"  
Height: 32.5"  
Weight: 35lbs  
EPA: 2.6ft<sup>2</sup>

Traditional  
ordering guide



ordering logic

model			model (cont)		
TRA30		30" Traditional	TRA30		30" Traditional
lens material			mounting options		
<input type="checkbox"/>	A	acrylic	<input type="checkbox"/>	PT	post top
<input type="checkbox"/>	P	polycarbonate	<input type="checkbox"/>	PM	pendant
lens finish			color (see page 33 for additional information)		
<input type="checkbox"/>	C	clear	<input type="checkbox"/>	BB	black
<input type="checkbox"/>	F	frosted	<input type="checkbox"/>	BZ	bronze
<input type="checkbox"/>	S	seeded	<input type="checkbox"/>	BG	green
<input type="checkbox"/>	W	white	<input type="checkbox"/>	BW	white
<input type="checkbox"/>			<input type="checkbox"/>	BY	gray
<input type="checkbox"/>			<input type="checkbox"/>	RAL	RAL _____
<input type="checkbox"/>			<input type="checkbox"/>	OTHER	_____
source					
<input type="checkbox"/>	LED	60 & 90W			
<input type="checkbox"/>	QL	55 & 85W Induction			
<input type="checkbox"/>	PSMH	50 - 150W			
<input type="checkbox"/>	HPS	50 - 150W			
<input type="checkbox"/>	CF	13 - 42W			
<input type="checkbox"/>	INC	150W			
optics					
<input type="checkbox"/>	IND3	indirect type III (LED)			
<input type="checkbox"/>	IND5	indirect type V (LED)			
<input type="checkbox"/>	DIR2	direct type II (LED)			
<input type="checkbox"/>	DIR3	direct type III (LED)			
<input type="checkbox"/>	DIR4	direct type IV (LED)			
<input type="checkbox"/>	DIR5	direct type V (LED)			
<input type="checkbox"/>	SR3	segmented reflector type III			
<input type="checkbox"/>	SR4	segmented reflector type IV			
<input type="checkbox"/>	SR5	segmented reflector type V			
<input type="checkbox"/>	GR3	glass refractor type III			
<input type="checkbox"/>	GR5	glass refractor type V			
<input type="checkbox"/>	FGCH	frosted glass chimney (n/a w/LED)			
<input type="checkbox"/>	3CD	triple candelabra (n/a w/LED)			
<input type="checkbox"/>	BL	bare lamp			
electrical options					
<input type="checkbox"/>	FS	fusing			
<input type="checkbox"/>	PEC	photocell			
<input type="checkbox"/>	QRS	quartz restrrike			
<input type="checkbox"/>	IQ	lamp/ballast diagnostics			
<input type="checkbox"/>	LSP	lightning surge protector			

**footnotes:**

- IND and DIR optics require LED source, LED source requires IND or DIR optics.
- FGCH & 3CD options are optionally energized when SR optics are selected (please consult factory for accommodation).
- Factory suggests that BL option is selected only when a low wattage source is used in conjunction with non-clear lenses.
- Medium socket is standard for all HID sources under 250W.
- LED and CF sources utilize a 120-277 voltage-sensing electronic driver, HID sources utilize a Quad-Tap (120, 208, 240 & 277V) core & coil magnetic ballast, consult factory for 347 or 480V. 12VDC LED drivers are available for solar power assembly integration, consult factory.
- QL induction source shall be supplied at 4000K (CCT), specify if 3000K is required.
- LED source shall be supplied at 4500K (CCT), specify is other color temp. is required (minimum quantities may apply).