



- 31" Treviso
- Railroad Scroll Arm

TRE31

Width: 18"
Height: 30.75"
Weight: 50lbs
EPA: 1.2ft²

Treviso
ordering guide



ordering logic

model

TRE31 31" Treviso

source

- LED 60 & 90W
- PSMH 50 - 150W
- HPS 50 - 150W
- CF 13 - 42W
- INC 150W

optics

- IND3 indirect type III (LED)
- IND5 indirect type V (LED)
- DIR2 direct type II (LED)
- DIR3 direct type III (LED)
- DIR4 direct type IV (LED)
- DIR5 direct type V (LED)
- SR3 segmented reflector type III
- SR5 segmented reflector type V

electrical options

- FS fusing
- PEC photocell
- QRS quartz restrike
- IQ lamp/ballast diagnostics
- LSP lightning surge protector

mounting options

- PT post top
- PM pendant w/ lower finial

model (cont)

TRE31 31" Treviso

color (see page 33 for additional information)

- BB black
- BZ bronze
- BG green
- BW white
- BY gray
- RAL RAL _____
- OTHER _____

footnotes:

1. Medium socket is standard for all HID sources under 250W.
2. DIR optics require LED source, LED source requires DIR optics.
3. LED and CF sources utilize a 120-277 voltage-sensing electronic driver, HID sources utilize a Quad-Tap (120, 208, 240 & 277V) core & coil magnetic ballast, consult factory for 347 or 480V. 12VDC LED drivers are available for solar power assembly integration, consult factory.
4. LED source shall be supplied at 4500K (CCT), specify is other color temp. is required (minimum quantities may apply).