



**VIN30**

Width: 11.5  
Height: 30"  
Weight: 25lbs  
EPA: 1.1ft<sup>2</sup>

Vinoy  
ordering guide

Luminaires



- 30" Vinoy Luminaire
- Vinoy Arm
- Vinoy Post
- Old Scroll Bench
- Santa Fe Receptacle
- CMB Bollard

## ordering logic

### model

VIN30 30" Vinoy

### lens material

P polycarbonate

### lens finish

CT clear textured  
 WT white textured

### source

LED 24, 48 & 70W  
 PSMH 50 - 150W  
 HPS 50 - 150W  
 CF 13 - 42W  
 INC 150W

### optics

DIR2 direct type II (LED)  
 DIR3 direct type III (LED)  
 DIR4 direct type IV (LED)  
 DIR5 direct type V (LED)  
 GR3 glass refractor type III  
 GR5 glass refractor type V  
 BL bare lamp

### electrical options

FS fusing  
 PEC photocell  
 QRS quartz restrike  
 IQ lamp/ballast diagnostics  
 LSP lightning surge protector

### mounting options

PM pendant

### model (cont)

VIN30 30" Vinoy

### color (see page 33 for additional information)

BB black  
 BZ bronze  
 BG green  
 BW white  
 BY gray  
 RAL RAL \_\_\_\_\_  
 OTHER \_\_\_\_\_

### footnotes:

1. Medium socket is standard for all HID sources under 250W.
2. DIR optics require LED source, LED source requires DIR optics.
3. LED and CF sources utilize a 120-277 voltage-sensing electronic driver, HID sources utilize a Quad-Tap (120, 208, 240 & 277V) core & coil magnetic ballast, consult factory for 347 or 480V. 12VDC LED drivers are available for solar power assembly integration, consult factory.
4. LED source shall be supplied at 4500K (CCT), specify is other color temp. is required (minimum quantities may apply).