



AA-34


Gemini Crossarm & Wall Bracket

Project Information

Name Location: _____ / _____
 Type / Quantity: _____ / _____
 Sold to: _____
 PO#: _____


Approvals

Crossarm Details



Note: All standard dimensions remain unchanged for Ø4", Ø5" and Ø6" poles

Wall Bracket Details



Specifications

Construction:

All cast aluminum parts shall be low copper alloy A356. All extruded aluminum parts shall be alloy 6061-T6, 6063-T5 or equal.

Crossarm Installation:

The crossarm is designed to slip over an 8" section of the pole top and is secured with six stainless steel set screws. The mounting adaptor shall be designed for 1.5G vibration conditions, when used with a Beacon Products luminaire.

Wall Bracket Installation:

The wall bracket is anchored to the wall by four mounting bolts, which are not provided by Beacon as the type and size (maximum diameter of 3/8") and depth will vary according to the type of wall. The maximum projection of the mounting bolts is 1.25". The junction box is not supplied by Beacon, however the bracket was designed to conceal a fully recessed rectangular single-gang junction box.

EPA (Effective Projected Area):

EPA is defined as (Surface Area x Drag Factor). Allowable Pole, Luminaire Arm, Luminaire and Accessory EPAs are derived from the most current published AASHTO standard (American Association of State Highway and Transportation Officials), currently AASHTO 2001. Customer assumes all responsibility for selecting the appropriate pole for installation. Luminaire Arm, Luminaire and Accessory EPA must be equal to or less than allowable EPA of pole. Consult a professional engineer for compliance with local codes and standards.


Fasteners:

All fasteners (where provided) shall be stainless steel. When tamper resistant fasteners are required, spanner HD (snake eye) style shall be provided (special tool required, available at additional cost).


Finish:

Finish shall be Beacote III polyester powdercoat electrostatically applied and thermocured. Wall brackets shall be subjected to iron phosphate chemical pretreatment prior to painting by immersion process.

Luminaire Mounting Details



Wall Mounting Details



Ordering Example:

AA34 / S / 4 / B / P / BB

AA-34 / / / / / / / /

see note*

Pole Shaft Profile

- W Wall
- S Smooth
- F Fluted

Pole Shaft Ø

- W Wall
- 4 4"
- 5 5"
- 6 6"

*Specify the above if a non-Beacon pole will be used

Arrangement | EPA index (ft²) / weight (lbs)

Shaft Ø	Wall	Weight	12lbs	-	-	-	-	-	-	-	-
	Ø4"	EPA	-	2.25	3.65	3.65	-	3.65	3.65	-	-
Ø5"	Weight	-	13lbs	20lbs	21lbs	-	27lbs	28lbs	-	-	-
	EPA	-	2.46	3.86	3.86	3.04	3.86	3.86	4.03	5.02	5.02
Ø6"	Weight	-	14lbs	21lbs	22lbs	21lbs	28lbs	29lbs	28lbs	35lbs	36lbs
	EPA	-	2.56	3.96	3.96	3.14	3.96	3.96	4.13	5.12	5.12
	Weight	-	16lbs	23lbs	24lbs	23lbs	30lbs	31lbs	30lbs	37lbs	38lbs

Finish

- BB black
- BZ bronze
- BG green
- BW white
- BY gray
- RAL RAL-
- OTHER

Consult factory for premium and verde finishes. Custom colors available.

Luminaire Mounting

- T Tenon
- P Pendant
- S Side